Kawasaki

`78 ~ `80 Model

Part No. 99926-1004-01

Service Specifications Handbook

This Service Specifications Handbook covers only the '78 '79 & '80 models.
Refer to the following Service Specifications Handbooks for olders models.

Part No.	Model	Part No.	Model
99997-901	~ '72	99926-1001-01	'75, '76, '77
99997-753	'73, '74	99926-1002-01	'76, '77, '78
99997-858-01	'73, '74, '75	99926-1003-01	'77, '78, '79
99997-887-01	'74, '75, '76		

ABBREVIATION

Ⓐ : Australian Model
Ⓑ : English Model
Ⓒ : Canadian Model
Ⓔ : European Model
Ⓕ : French Model
Ⓖ : German Model
Ⓘ : Italian Model
Ⓙ : Japanese Model
Ⓝ : Norwegian Model
Ⓞ : General Model
Ⓢ : South African Model
Ⓣ : Thai Model
Ⓤ : U.S. Model
Ⓦ : Swiss Model
Ⓓ : Charging current at Daytime
Ⓝ : Charging current at Nighttime
L/T : Leading/trailing shoes drum brake
2L : Two leading shoes drum brake

© Kawasaki Heavy Industries, Ltd. 1980
Feb. 1980. ①. 3 Ⓚ

Contents

1. Specifications 6
2. Engine 42
3. Carburetor 76
4. Clutch & Transmission 110
5. Electrical Equipment 1 144
6. Electrical Equipment 2 178
7. Frame 212
8. Dimensions, Performance 246
9. Conversion Table 282

NOTE:

Kawasaki Heavy Industries, Ltd. accepts no liability for any inaccuracies or omission in this publication, although every possible care has been taken to make it as complete and accurate as possible. All specifications subject to change without prior notice, and may not apply to every country.

Displacement		750 ~ 1,300 cc				
Model year		'80	'80	'80	'78	'78 Late
Item \ Model		KZ750-E1	KZ750-G1	KZ750-H1	KZ1,000-A2	KZ1,000-A2A
CARBURETOR	Type	Keihin CV34	Mikuni BS38	Keihin CV34	Mikuni VM26SS	←
	Main jet	Primary 62 Secondary 125	125-R	Primary 62 Secondary 125	105-R	102.5-R
	Needle jet		Y-3 Ⓒ Z-4		O-5	O-3
	Jet needle	N01A	4HL14 Ⓒ 4JN19-4	N01A	5DL31-3	5CN7-4
	Pilot jet	38	40 Ⓒ 45	38	15	←
	Cutaway				1.5	2.0
	Air screw or pilot screw [Turns, backed out]	2.0	1 1/2 Ⓤ	2.0	1.0	
	Service fuel level mm [From the edge of the carburetor body to the fuel level]	4 ± 1	5.5 ± 1	4 ± 1	3 ± 1	←

Displacement		750 ~ 1,300 cc				
Model year		'79	'79 Late	'80	'78	'79
Item \ Model		KZ1,000-A3	KZ1,000-A3A	KZ1,000-A4	KZ1,000-D1	KZ1,000-D2
CARBURETOR	Type	Mikuni VM26SS Ⓐ VM28SS	Mikuni VM28SS	←	←	←
	Main jet	105-R Ⓤ 102.5-R	←	←	107.5-R	105-R Ⓤ 102.5-R
	Needle jet	O-1 O-6	O-1 Ⓤ O-4	O-4	O-1	O-1 Ⓤ O-4
	Jet needle	5CN15-3 Ⓤ 5CN18-3	5CN15-3 Ⓤ 5CN17-3	5CN17-3 Ⓤ 5CN29	5CN15-3	5CN15-3 Ⓤ 5CN17-3
	Pilot jet	15	←	←	←	←
	Cutaway	1.5 2.0 Ⓐ 1.75	1.75 Ⓤ 2.0	2.0	1.5	1.75 Ⓤ 2.0
	Air screw or pilot screw [Turns, backed out]	Ⓐ 1¼ Ⓤ	1¼ Ⓤ 1⅛		1⅝	1¼ Ⓤ
	Service fuel level mm [From the edge of the carburetor body to the fuel level]	4 ± 1	←	←	←	←

Displacement		750 ~ 1,300 cc				
Model year		'80	'79	'80	'79	'80
Item \ Model		KZ1,000-D3	KZ1,000-E1	KZ1,000-E2	KZ1,300-A1	KZ1,300-A2
CARBURETOR	Type	Mikuni VM28SS	←	←	Mikuni BSW32	←
	Main jet	105-R Ⓤ 102.5-R	110-R	←	110-R Ⓖ 105-R	110-R
	Needle jet	O-1 Ⓤ O-4	←	←	Y-8	←
	Jet needle	5CN15-3 Ⓤ 5CN29	5CN15-3 Ⓤ 5CN17-3	5CN15-3 Ⓤ 5CN29	5P3-3 Ⓤ 5P2-3	5P3-3 Ⓤ 5P4
	Pilot jet	15	←	←	42.5	←
	Cutaway	1.75 2.0	←	←		
	Air screw or pilot screw [Turns, backed out]	1¼ Ⓤ	←	←	Ⓖ 1¾	
	Service fuel level mm [From the edge of the carburetor body to the fuel level]	4 ± 1	←	←	7.5 ± 1	←